Cable Shears

95

- for cutting copper and aluminum cables, single and multi-stranded wire
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- easy cutting with one-hand operation
- pinch guard prevents operators´ fingers being pinched
- adjustable bolted joint, self-locking
- high-grade special tool steel; forged, oil-hardened

Style 2
Internal opening spring, protected and captive

Style 4
Multifunctional tool for working on NYM cable from 3 x 1.5 mm² to 5 x 2.5 mm² (cutting, stripping insulation); universal stripping area for both solid conductor cross-sections; reliable alignment of the cable in the stripping area due to V-shaped blade geometry

95 12 165 T BKA*
Pliers with integrated tether attachment point for tool drop protection system

Cut performed with a Diagonal Cutter: high effort required, inaccurate cut, considerable deforming and crushing of the cable



Cut performed with a Cable Shear: easy, clean cut without any deformation of the cable

The locking device keeps shears with spring inside the joint closed

95 11 165

95 12 165

95 12 165 T BKA

95 18 165 US
1000 V ASTM

95 21 165

95 41 165

Product Number	Packaging	↔ Inch mm		Tool	Handles	Style	Cutting capacities Ø Inch Ø mm	Cutting capacities mm²	AWG	lbs
95 11 165	X	6 1/2 165		burnished	plastic coated	1	19/32 15	50	1/0	0.49
95 12 165	X	6 1/2 165		burnished	multi-component grips	1	19/32 15	50	1/0	0.55
95 12 165 T BKA	X	6 1/2 165		burnished	multi-component grips, integrated tether attachment point	1	19/32 15	50	1/0	0.56
95 18 165 US	X	6 1/2 165	1000 V ASTM	burnished	insulated, multi-component grips, ASTM-tested	1	19/32 15	50	1/0	0.58
95 21 165	X	6 1/2 165		burnished	plastic coated	2	19/32 15	50	1/0	0.50
95 22 165		6 1/2 165		burnished	multi-component grips	2	19/32 15	50	1/0	0.56
95 41 165		6 1/2 165		burnished	plastic coated	4	15/32 12	35	1/0	0.49

*Learn more about our tethered tool system on pages 207-211