

**DEWALT****20V**^{MAX*}
BRUSHLESS**XR**[®]

BEST CONTROL WITH FASTEST MATERIAL REMOVAL VS. LEADING COMPETITORS**

DCW211B **20V MAX* XR[®]** **5 IN. RANDOM** **ORBITAL** **SANDER** **(TOOL ONLY)**

Designed to maximize productivity for the professional woodworker, remodeler, carpenter and general contractor, the 20V MAX* XR[®] 5 in. Random Orbital Sander offers the best control with fastest material removal vs. leading competitors** (battery and charger sold separately). Ideal for small surfaces and tight spaces, this sander sands up to 50 sq.-ft. and leaves a fine finish††. As our best performing 20V MAX* 5 in. random orbital sander, the 20V MAX* XR[®] 5 in. Random Orbital Sander delivers fast material removal, adjustable speed, and outstanding control‡‡.



Battery sold separately

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

**vs. leading competitors' cordless 5" random orbit sanders; vibration based on steel plate, 50N bias force, 180 grit; material removal based on pine, 3kg bias force, 80 grit.

††Per charge, on high speed, removing 3.8g, 80 grit, 3kg bias force on pine, using DCB205 (sold separately).

‡‡Material removal rate and vibration using DCB205 (sold separately).

DCW211BSS

20V MAX* XR® 5 IN. RANDOM ORBITAL SANDER (TOOL ONLY)

EQUIPPED WITH DEWALT® AIRLOCK™ SYSTEM

Collects up to 95% of dust*** (dust extractors sold separately)

HELP MINIMIZE CLEAN-UP

WIRELESS TOOL CONTROL enables vacuum operation (vacuum sold separately)

WORK IN CONFINED AREAS

Our lowest profile 5 in. random orbital sander†

HOOK AND LOOP 8-HOLE PLATEN/PAD

PERFORM PROTECT ANTI-VIBRATION

CHIP-READY TRACK THIS TOOL

DEWALT® Chip Sold Separately.

VARIABLE SPEED CONTROL

5 speeds from 8,000 - 12,000 (no load) OPM

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

***On high speed, 80 grit, 3kg bias force on oak, using DWV015 (sold separately).

†On high speed, 180 grit, 50N bias force on steel plate using DCB205 battery (sold separately) vs. DCW210.

‡Height, tool only

DEWALT PERFORM & PROTECT™ line of tools is designed to provide a high level of one or more of the following: dust containment, control, or low vibration, without sacrificing performance.



MINIMIZE FATIGUE: Up to 40% less vibration†



WORK IN CONFINED AREAS: Our lowest profile 5 in. random orbital sander‡

SPECIFICATION

ORBITS PER MINUTE	8,000-12,000 (no load) OPM
ORBIT DIAMETER	7/64 in.
HEIGHT	4.37 in.
PAD TYPE	Hook and Loop

WARRANTY

TOOL WARRANTY

3
YEAR

LIMITED WARRANTY

1
YEAR

FREE SERVICE

90
DAY

MONEY BACK GUARANTEE

PRODUCT OFFERINGS

DCW211B

(1) DCW211 20V MAX* XR® 5 in. Random Orbital Sander (Tool Only)

(1) 8 Hole 80 Grit Sandpaper

(1) DCE042 TOOL CONNECT™ Chip Adapter (chip sold separately)



RELATED PRODUCTS

DCW230B

20V MAX* XR® 6 in. Random Orbital Sander (Tool Only)



DCW200B

20V MAX* XR® Brushless Cordless 1/4 Sheet Variable Speed Sander (Tool Only)



DCW220B

20V MAX* XR® 3 in. x 21 in. Brushless Cordless Belt Sander (Tool Only)



DCW211PAD

DEWALT® Replacement Pad for DCW211 5-in. Random Orbital Sander

