

DEWALT**20V^{MAX}**
BRUSHLESS**XR**

THE FASTEST MATERIAL REMOVAL WITH LOWEST VIBRATION VS. LEADING COMPETITORS**

DCW230B**20V MAX^{*} XR[®]
6 IN. RANDOM
ORBITAL
SANDER
(TOOL ONLY)**

The 20V MAX^{*} XR[®] 6 in. Random Orbital Sander delivers the fastest material removal with the lowest vibration vs. leading competitors** (battery and charger sold separately). Ideal for large wood surfaces, this product sands up to 200 sq.-ft. to keep you moving on big jobs†. With variable speeds from 6,000 to 10,000 (no load) OPM this sander adapts to the task at hand, leaving a fine finish. Equipped with the DEWALT[®] AirLock™ system to help maintain a clean work environment, this product collects up to 95% of dust when using a compatible DEWALT[®] dust extractor (sold separately)‡.

**CARPENTRY**
TOTAL SOLUTIONS

Battery sold separately

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

**cordless 6" random orbit sanders; material removal based on pine, 80 grit, 3kg bias force; vibration based on steel plate, 180 grit, 50N bias force.

†Per charge, using DCB2108 (sold separately), regarding up to 200 sq.ft. removing 3.8g of pine, on high speed, 80 grit, 3kg bias force runtime on high speed, using 80 grit, 3kg bias

‡On high speed, 80 grit, 3kg bias force on oak using DWV015 (sold separately).

DCW230BSS

20V MAX* XR® 6 IN. RANDOM ORBITAL SANDER (TOOL ONLY)

EQUIPPED WITH DEWALT® AIRLOCK™ SYSTEM

Collects up to 95% of dust*
(dust extractors sold separately)

HELP MINIMIZE CLEAN-UP

WIRELESS TOOL CONTROL
enables vacuum operation
(vacuum sold separately)



CHIP-READY
TRACK THIS TOOL
DEWALT® Chip Sold
Separately.

VARIABLE SPEED CONTROL

5 speeds from 6,000 - 10,000
(no load) OPM

HOOK AND LOOP 14-HOLE PLATEN/PAD

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.
†Per charge, using DCB2108 (sold separately), regarding up to 200 sq.ft. removing 3.8g of pine, on high speed, 80 grit, 3kg bias force runtime on high speed, using 80 grit, 3kg bias.
‡On high speed, 80 grit, 3kg bias force on oak using DWV015 (sold separately).
††vs. leading competitors' cordless 6" random orbit sanders, 180 grit, 50N bias force on steel plate.
DEWALT PERFORM & PROTECT™ line of tools is designed to provide a high level of one or more of the following: dust containment, control, or low vibration, without sacrificing performance.

Battery sold separately



LONG RUNTIME: Sand up to 200 sq.-ft.†

Battery sold separately



MINIMIZE FATIGUE: Lowest vibration vs. leading competitors††

SPECIFICATION

ORBITS PER MINUTE	6,000-10,000 (no load) OPM
ORBIT DIAMETER	13/64 in.
HEIGHT	4.98 in.
PAD TYPE	Hook and Loop

WARRANTY

TOOL WARRANTY

3
YEAR
LIMITED
WARRANTY

1
YEAR
FREE
SERVICE

90
DAY
MONEY BACK
GUARANTEE

PRODUCT OFFERINGS

DCW230B

- (1) DCW230 20V MAX* XR® 6 in. Random Orbital Sander (Tool Only)
- (2) 14 Hole 80 Grit Sandpaper
- (1) DCE042 TOOL CONNECT™ Chip Adapter (chip sold separately)



RELATED PRODUCTS

DCW211B

20V MAX* XR® 5 in. Random Orbital Sander (Tool Only)



DCW200B

20V MAX* XR® Brushless Cordless 1/4 Sheet Variable Speed Sander (Tool Only)



DCW220B

20V MAX* XR® 3 in. x 21 in. Brushless Cordless Belt Sander (Tool Only)

